

Product data sheet

Specifications



impulse relay TL - 2P - 2 NO - 16A -
coil 130 VAC 50/60Hz- 48 VDC

15521

! Discontinued on: 01 April 2019

! Discontinued

Main

Product or component type	Impulse relay
Device short name	TL
Device application	Remote control
Poles	2P
Pole contact composition	2 NO
[In] rated current	16 A
Network type	AC
[Uc] control circuit voltage	130 V AC 50/60 Hz 48 V DC

Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	250 V AC 50/60 Hz
Control type	Coil disconnection Remote control
Control signal type	Impulse
Switching frequency	100 switching operations/day 5 switching operations/minute
Impulse duration	50 ms...1 s
Remote control type	Illuminated push-button 3 mA
Local signalling	ON/OFF indication
Mounting mode	Fixed
Mounting support	DIN rail
9 mm pitches	2
Height	84 mm
Width	18 mm
Depth	60 mm
Electrical durability	AC-21: 200000 cycles AC-22: 100000 cycles
Range compatibility	ATEt ATL

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Standards	EN 669-1 EN 669-2-2
Product certifications	GOST
Quality labels	IMQ NF VDE CEBEC
Noise level	60 dB
Tropicalisation	2
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-20...50 °C

Packing Units

Package 1 Weight	0.112 kg
Package 1 Height	0.850 dm
Package 1 width	0.180 dm
Package 1 Length	0.720 dm

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)

15521 is replaced by:

1x



impulse relay iTL - 2P - 2 NO - 16A - coil 130 VAC 50/60Hz- 48 VDC
A9C30312