

Product data sheet

Specifications



extension ETL - 2P - 1C/O + 1NO -
16A - coil 130VAC 50/60Hz 48VDC

15531

! Discontinued on: 05 April 2019

! Discontinued

Main

Product or component type	Extension for impulse relay
Device short name	ETL
Relay application	Remote control
Poles description	2P
Pole contact composition	1 C/O + 1 NO
[In] rated current	16 A
Network type	AC

Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	250 V AC 50/60 Hz
Control type	Remote control Toggle
Control signal type	Impulse
Switching frequency	5 switching operations/minute
Impulse duration	50 ms
Remote control type	Illuminated push-button 3 mA
Local signalling	ON/OFF indication
[Uc] control circuit voltage	130 V AC 50/60 Hz 48 V DC
Supply inrush power	19 VA
Mounting mode	Fixed, on right side of TL
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Height	84 mm
Width	18 mm
Depth	60 mm
Colour	Grey
Electrical durability	AC-21: 200000 cycles AC-22: 100000 cycles

Connections - terminals	Tunnel type terminals - <= 10 mm ²
Auxiliary connection terminal	Tunnel type terminalscontrol circuit in 0.5...6 mm ²

Environment

Standards	EN 669-1 EN 669-2-2
Product certifications	VDE NF GOST CEBEC IMQ
Noise level	60 dB
Tropicalisation	2
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-20...50 °C

Packing Units

Package 1 Weight	0.126 kg
Package 1 Height	0.300 dm
Package 1 width	0.770 dm
Package 1 Length	0.870 dm

Contractual warranty

Warranty	18 months
-----------------	-----------

Recommended replacement(s)

15531 is replaced by:

1x



extension iETL iTL 16 - 2P - 1C/O + 1NO - 16A - coil 130VAC 50/60Hz - 48VDC
A9C32316